

PEB 720 - Technical Specifications

Material Handling | Bias | IND-3 | TT/TL | 5 Years



Salient Features & Benefits

Port Equipment Bias 720 tires, specially designed for as RTGs, Empty Container handler in port applications

Superior traction and excellent performance:

- Sturdy lug design
- Provides Excellent grip in operation.

Suitable for heavy-duty applications:

- Robust construction.
- High load carrying capacity which used in stacking and loading applications.

Excellent Durability:

- Reinforced sidewalls & bead area.
- Provide resistance against cuts & scrapes

Maximum operating efficiency:

- Abrasion & wear resistance Tread compound.
- Minimizes wear in heavy-duty loading applications, resulting longer tire life.

Less downtime in Port Application:

- Deep Wide Tread Grooves
- Reduce the risk of groove cracks and heat buildup in operation.

Machineries



Empty Container Handler Gantry Crane

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	14.00-24
Rec Rim	10.0WA/VA(TL)/10.0W(TT)
Alternate Rim	-
PR & LI/SI	28PR 188A2
Section Width (mm)	375
Overall Diameter (mm)	1370
Static Load Radius (mm)	619
Rolling Circumference (mm)	4098
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	6.5	9.3
10	-	10000
50	5600	-