

PEB 720 - Technical Specifications

Material Handling | Bias | IND-3 | TT/TL | 5 Years



Salient Features & Benefits

Port Equipment Bias 720 tires, specially designed for as RTGs, Empty Container handler in port applications

Superior traction and excellent performance:

- Sturdy lug design
- Provides Excellent grip in operation.

Suitable for heavy-duty applications:

- Robust construction.
- High load carrying capacity which used in stacking and loading applications.

Excellent Durability:

- Reinforced sidewalls & bead area.
- Provide resistance against cuts & scrapes


Maximum operating efficiency:

- Abrasion & wear resistance Tread compound.
- Minimizes wear in heavy-duty loading applications, resulting longer tire life.

Less downtime in Port Application:

- Deep Wide Tread Grooves
- Reduce the risk of groove cracks and heat buildup in operation.

Machineries



Empty Container Handler Gantry Crane

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	21.00-25
Rec Rim	15.00/3.0
Alternate Rim	-
PR & LI/SI	40PR
Section Width (mm)	570
Overall Diameter (mm)	1750
Static Load Radius (mm)	777
Rolling Circumference (mm)	5234
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	10
10	27810
25	25750