

## PEB 721 - Technical Specifications

Material Handling | Bias | IND-4 | TT/TL | 5 Years



### Salient Features & Benefits

**Port Equipment Bias 721, specially designed for container handling equipment in Port applications:**

#### Maximum Operating hours:

- Deep Tread with Higher Base coverage.
- Provides longer service life.

#### Less downtime in the Port Application:

- Heat & Abrasion Resistance Compound.
- Quick heat dissipation and cooler running on a hard concrete surface.

#### High load-carrying capacity:

- Strong Casing.
- Suitable for heavy-duty applications.

#### Excellent Durability:

- Reinforced sidewalls & bead area.
- Provide resistance against cuts & scrapes


#### Outstanding Stability and Manoeuvrability:

- High Rubber Mass at Tread Centre.
- Maximum operating efficiency and exceptional stability in lift mode

## Machineries



Empty Container Handler



Reach Stacker

**Standard:** ProductComponent.International Standards

## Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	18.00-33
Rec Rim	13.00/2.5
Alternate Rim	-
PR & LI/SI	40PR
Section Width (mm)	510
Overall Diameter (mm)	1887
Static Load Radius (mm)	852
Rolling Circumference (mm)	5644
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Load Capacity

	km/h / bar	10.3
	10	26325
	25	24375